

Eaton C10G2

Catalog Number: C10G2

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 2 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CHM Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C10G2
	Model Code
	CYLINDRICAL FUSE 10 x 38 2A GG 500V AC
EAN	UPC
5027590493468	051712754224
Product Length/Depth	Product Height
38 mm	10 mm
Product Width	Product Weight
10 mm	8.2 g
Compliances	Certifications
RoHS Compliant	IEC 60269
CE Marked	
GoST-R	

Electrical data

Amperage Rating

2 A

Voltage rating

500 V

Voltage type

AC

Breaking capacity

120 kA

Utilization category

gL/gG (cable protection/equipment protection)

Frequency rating - max

62 Hz

Compatible fuse holder

Suitable for

CHM Modular fuse holder

Resources

Catalogues

CA134002EN

Compliance information

CE C08G, C08M, etc cylindrical fuselinks

UKCA C08G, C08M, etc cylindrical fuselinks

Multimedia

Video Cylindrical fuse link portfolio

Technical data sheets

720115 Cylindrical fuses

Technical service bulletins

Datasheet - C10G2



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia