

6

High speed fuses

Square body fuse accessories

Indicator systems

Typower ZILOX fuses are available with three different indicator systems.

1. Visual indicator

The indicator situated in one cover plate is clearly visible as soon as the fuse has operated. The minimum voltage for operating the indicator is 20V.

2. Type T indicator

The indicator is situated on one cover plate with a cover plate tag to accommodate an auxiliary switch. The minimum voltage for operating the indicator is 20V. A special low voltage indicator (1.5V) is available on request.

3. Type K indicator

This indicator is situated on the fuse body. It is covered by an adapter for snap-on mounting of an auxiliary switch. The operating voltage of the indicator is 1.5V. As a matter of safety, the factory mounted adapter must not be removed from the fuse.

Microswitch

The Typower ZILOX fuses with either type T indicator or type K indicator can be equipped with a microswitch for remote electrical indication of fuse operations. All microswitches have one normally open and one normally closed contact. Ratings are 2A, 250Vac.



Microswitch	6.3 x 0.8mm Lugs	2.8 x 0.5mm Lugs	Indicator Type	Amps
170H0235	X		T	2
170H0236	X		T	2
170H0237		X	T	2
170H0238		X	T	2
170H0069	X		K	2
BUL50	-	-	-	6

Size	DIN 43 653		DIN 43 620		French Style		Flush End		US Style	
	Type T	Type K	Type T	Type K	Type T	Type K	Type T	Type K	Type K	Type K
000	170H0236		170H0236							
	170H0238		170H0238							
00	170H0235						170H0235			
	170H0237						170H0237			
1*	170H0235	170H0069	170H0235		170H0236	170H0069			170H0069	170H0069
	170H0237		170H0237		170H0238					
1	170H0235	170H0069			170H0236	170H0069			170H0069	170H0069
	170H0237				170H0238					
2	170H0235	170H0069	170H0235		170H0236	170H0069			170H0069	170H0069
	170H0237		170H0237		170H0238					
3	170H0235	170H0069	170H0236		170H0236	170H0069			170H0069	170H0069
	170H0237		170H0238		170H0238					
4									170H0069	
23									170H0069	
24									170H0069	