

Fuse bases (blocks)

DIN 43 653 fuse bases

For the Typower ZILOX fuses according to DIN 43 653, the following fuse bases are available:

Catalog number	Max volts	Amp rating	Center distance
170H3003	1000	630	80mm
170H3004	1000	1250	80mm
170H3005	1400	630	110mm
170H3006	1400	1250	110mm

The fuse bases rated 1250A can also be used for the fuses with higher rated current if the maximum load current is derated according to the table below:

Fuse amp rating	Max amp load in fuse base
1400	1325
1500	1400
1600	1500
1800	1650
2000	1800

Fixed center base style	Max volts	Max. fuse amp rating	Fuse size
170H1007	1000	400	00_000
170H1013	660	200	0000_000

UL Recognized to UL 512.

Universal fuse bases

For the Typower ZILOX fuses according to DIN 43 653, French style and North American style, the following fuse bases are available:

Modular base style	Max volts	Max. fuse amp rating	Data Sheet
1BS101	600	100	1206
1BS102	600	400	1207
1BS103	600	400	1208
1BS104	600	600	1209
BH-0xxx	700	100	1200
BH-1xxx	2500	400	1201
BH-2xxx	5000	400	1202
BH-3xxx	1250	700	1203

Modular fuse bases are UL Recognized to UL 512 and meet the spacing requirements of UL 347. Contact your Eaton sales representative for more complete ordering information.

DIN 43 620 fuse bases

Size	Part number
000-00	SD00-D
1*, 1	SD1-D
2,3	SD2-D

