

connection terminal for PE/N bar (01114)



The picture may show a similar product.

Description

Part No.: **01114** 000

CRITO[®]

connection terminal for PE/N bar

35 mm²

suitable for PE and N busbars 01126 - 01130

Product group 07

Subgroup 06

pack size 100

EAN 4021267011147

ETIM 5.0 EC002498

ETIM 8.0 EC002498

Approvals

Standards

IEC 61439-1:2020
IEC 60999-1:1999
IEC 60999-2:2003

CCC approval: no certification required

Technical data

Details IEC

Standards

IEC 61439-1:2020
IEC 60999-1:1999
IEC 60999-2:2003

Electrical data IEC

rated voltage (IEC) AC: 400 V

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 0.0 W.
(The power dissipation at full load would be 0.0 W.)

Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

max. permitted voltage (IEC) AC: 500 V

Mechanical data

W x H x D: 15 x 15 x 15
weight: 1.4 kg/100

Terminal points

max. cross-section: 35 mm²

Not suitable for aluminium cables !

Terminal space: 7 x 7

1.5 - 25mm² flexible with wire-end ferrule

1.5 - 10mm² solid round

only for maximum tightening torque:

16mm² stranded round

Material properties

halogen-free: Yes

Application notes

Not suitable for aluminium cables !

<https://pim.woehner.de/EN/EN/1000045464>