

## universal busbar support (01485)



The picture may show a similar product.

### Description

Part No.: **01485 000**

universal busbar support

4-pole with internal screw holes

for busbars 12, 15, 20, 25, 30 x 5, 10

### System

60Classic

### Advantages of the product

With internal screw holes

can also be used as centre support

With the 4th pole, the width of the busbar can be set independent of L1, L2 and L3.

**Product group** 06

**Subgroup** 12

**pack size** 10

**EAN** 4021267014858

ETIM 5.0 EC001166

ETIM 8.0 EC001166

## Approvals

### Standards

IEC 61439-1:2020

UL 508

### Approvals

CSA , UL , DNV GL



type number: 485

UL file: E123577, UL category (for USA): NMTR2 <https://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR8 <https://www.ul.com>

CSA file: 110285, CSA class: 3211-37 <https://directories.csa-international.org>

CCC approval: no certification required

## Technical data

### Details IEC

#### Standards

IEC 61439-1:2020

#### Electrical data IEC

rated voltage (IEC) AC: 800 V

rated frequency (IEC): 50 / 60 Hz

rated isolation voltage  $U_i$  AC: 1000 V

rated surge voltage  $U_{imp}$ : 8 kV

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 0.0 W.

(The power dissipation at full load would be 0.0 W.)

### Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

min. permitted operation temperature -40°C

Kurzschlussfestigkeit:

Siehe Kurzschlussdiagramm im Bereich Download

### Details UL

#### Standards

UL 508

### Electrical data UL

rated voltage (UL) AC: 600 V

rated frequency (UL): 50 / 60 Hz

### Mechanical data

W x H x D: 20 x 245 x 51

weight: 26.6 kg/100

poles: 3-pole+N

for busbars: 12, 15, 20, 25, 30 x 5, 10

### Material properties

halogen-free: Yes

## Accessories

covers



**01131 000**

end cover

for busbar supports 01357 and 01485 (1x 01131 = 1 left + 1 right cover)

<https://pim.woehner.de/EN/EN/1000043931>