

holder for cylindrical fuses (31115)



The picture may show a similar product.

Description

Part No.: **31115 000**

AMBUS[®] Panel

holder for cylindrical fuses

14x51 / 1P

50 A / 690 V

for mounting rail

System

Panel

Advantages of the product

large clamping range

holder for label

Product group 17

Subgroup 09

pack size 6

EAN 4021267311155

ETIM 5.0 EC002705

ETIM 8.0 EC002705

Approvals

Standards

IEC 60947-1:2020

IEC 60947-3:2020 AC ratings only

UL 4248-1

Approvals

IEC (CB) , CSA , UL , CCC



for UL feeder circuits >250V

type number: AES14x51

UL file: E230163, UL category (for USA): IZLT <https://www.ul.com>

UL file: E230163, UL category (for Canada): IZLT7 <https://www.ul.com>

CSA file: 110285, CSA class: 6225-01 <https://directories.csa-international.org>

CCC certificate: 2004010302117255

Technical data

for fuse links size: 14x51

fuse links acc. to standard: IEC / HD 60269-2

permitted power dissipation of the fuse-link: 5 W

Details IEC

Standards

IEC 60947-1:2020

IEC 60947-3:2020 AC ratings only

Electrical data IEC

rated current (IEC): 50 A

rated voltage (IEC) AC: 690 V

rated isolation voltage U_i AC: 800 V

rated isolation voltage U_i DC: 800 V

rated surge voltage U_{imp} : 6 kV

cond. short-circuit current with fuses (AC): 100 kA / 400 V (50 A)

100 kA / 500 V (40 A)

80 kA / 690 V (25 A)

approved with fuse links of operation class: gG

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 0.6 W.

(The power dissipation at full load would be 0.9 W.)

Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

further utilisation category AC (IEC 60947-3): AC-20B (1000 V) at pollution degree 2

further utilisation category DC (IEC 60947-3): DC-20B (800 V)

A fuse-combination unit acc. to IEC 60947-3 can only be operated at a higher voltage than its rated voltage, if it is used as a fuse-disconnector without breaking capacity, up to its max. rated insulation voltage and labelled as such.

min. permitted operation temperature -40°C

for fuse links as per IEC / EN 60269-2 with permitted rated power dissipations

up to max. 5W for gG/gL

up to max. 3W for aM

Details UL

Standards

UL 4248-1

for UL feeder circuits $>250\text{V}$

suitable for field-installed conductors

Electrical data UL

rated current (UL): 50 A
rated voltage (UL) AC: 600 V
rated frequency (UL): 50 / 60 Hz
rated voltage (UL) DC: 600 V
for wires UL: Cu 75°C

SCCR: 100 kA

Mechanical data

W x H x D: 27 x 90 x 69
weight: 9.7 kg/100
poles: 1-pole
Mounting: for mounting rail

degree of protection: IP20
front degree of protection: IP20

Terminal points

cage clamp connection
screw drive: PZ2
wire stripping: 14 mm
min. cross-section: 1.5 mm²
max. cross-section: 35 mm²
Md min.: 2.5 Nm
Md max.: 3.0 Nm
Not suitable for aluminium cables !

min. cross-section UL: AWG 14
max. cross-section UL: AWG 2
torque (UL): 26 lb-in
for wires UL: Cu 75°C

Material properties

halogen-free: Yes

Application notes

Not suitable for aluminium cables !

A fuse-combination unit acc. to IEC 60947-3 can only be operated at a higher voltage than its rated voltage, if it is used as a fuse-disconnector without breaking capacity, up to its max. rated insulation voltage and labelled as such.

permitted power dissipation of the fuse-link: 5 W
for UL feeder circuits >250V

Accessories

accessories for mounting



31269 000

connection kit 14x51, 2-pole
for 10 2-pole combinations 14x51

connection accessories



01198 000A

connection terminal, front connection
25 - 95 mm²
for: 31057




31014 000A

comb-type busbar, 1-pole, bridge type, pitch 27 mm
80 A, 1 m long
16 mm²



31028 000A

connection terminal, side connection
6 - 50 mm²
for: 31014, 31024, 31309, 31311



31057 000A

comb-type busbar, 1-pole, bridge type, pitch 27 mm
130 A, 1 m long
35 mm²

<https://pim.woehner.de/EN/EN/1000051107>