

## cylindr. fuse link 16 A (31186)



The picture may show a similar product.

### Description

Part No.: **31186 000**  
cylindr. fuse link 16 A  
500 V, gG  
10 x 38

**Product group** 22  
**Subgroup** 21

**pack size** 10  
**EAN** 4021267311865

**ETIM 5.0** EC002704  
**ETIM 8.0** EC002704  
**ETIM 10.0** EC002704

# Approvals

## Standards

IEC 60269-1:2006 + A1:2009 + A2:2014  
IEC 60269-2:2013 + A1:2016, Fuse system F

# Technical data

size: 10x38

## Details IEC

### Standards

IEC 60269-1:2006 + A1:2009 + A2:2014  
IEC 60269-2:2013 + A1:2016, Fuse system F

### Electrical data IEC

rated current (IEC): 16 A  
rated voltage (IEC) AC: 500 V

operation class gG

rated short-circuit breaking capacity AC 120 kA

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 1.2 W.  
(The power dissipation at full load would be 1.9 W.)

## Mechanical data

W x H x D: 10 x 10 x 38  
weight: 0.6 kg/100

## Material properties

Material: Porcelain  
halogen-free: Yes

<https://pim.woehner.de/EN/EN/1000051515>