

cylindr. fuse link 25 A (31213)



The picture may show a similar product.

Description

Part No.: **31213** 000
cylindr. fuse link 25 A
690 V, gR
10 x 38

Product group 22
Subgroup 22

pack size 10
EAN 4021267312138

ETIM 5.0 EC002704
ETIM 8.0 EC002704
ETIM 10.0 EC002704

Approvals

Standards

IEC 60269-1:2006 + A1:2009 + A2:2014

IEC 60269-4:2009 + A1:2012 + A2: 2019

Approvals

IEC (CB) , UL



UL file: E180276, UL category (for USA): JFHR2 <https://www.ul.com>

Technical data

size: 10x38

Details IEC

Standards

IEC 60269-1:2006 + A1:2009 + A2:2014

IEC 60269-4:2009 + A1:2012 + A2: 2019

Electrical data IEC

rated current (IEC): 25 A

rated voltage (IEC) AC: 690 V

operation class gR

rated short-circuit breaking capacity AC 200 kA

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 4.4 W.

(The power dissipation at full load would be 6.8 W.)

Electrical data UL

rated voltage (UL) AC: 700 V

rated frequency (UL): 50 / 60 Hz

Mechanical data

W x H x D: 10 x 10 x 38

weight: 0.6 kg/100

Material properties

Material: Porcelain

halogen-free: Yes

<https://pim.woehner.de/EN/EN/1000051946>