

## busbar adapter 144 A, 3-pole (32660)



The picture may show a similar product.

### Description

Part No.: **32660** 000A

EQUES<sup>®</sup> 60Classic

busbar adapter 144 A, 3-pole

76 x 200

connection to the system top

for Siemens 3VA10, 3VA11

for busbars 12, 15, 20, 25, 30 x 5, 10 and section busbars

### System

60Classic

Product group 05

Subgroup 30

pack size 1

EAN 4021267326609

ETIM 5.0 EC001531

ETIM 8.0 EC001531

# Approvals

## Standards

IEC 61439-1:2020

CCC approval: no certification required

# Technical data

## Details IEC

### Standards

IEC 61439-1:2020

### Electrical data IEC

rated current (IEC): 144 A

rated voltage (IEC) AC: 690 V

rated isolation voltage  $U_i$  AC: 800 V

rated surge voltage  $U_{imp}$ : 6 kV

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 7.7 W.

(The power dissipation at full load would be 12.0 W.)

### Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

min. permitted operation temperature  $-40^{\circ}\text{C}$

## Mechanical data

W x H x D: 76 x 200 x 26

weight: 81.0 kg/100

poles: 3-pole

for busbars: 12, 15, 20, 25, 30 x 5, 10 and section busbars

## Material properties

halogen-free: Yes

## Application notes

There must be a clearance of at least 10 mm above the article to remove it from the busbar system.  
the short-circuit capacity of the combination of adapter and MCCB depends on the MCCB

<https://pim.woehner.de/EN/EN/1000157999>