

## NH fuse switch-disconnector size 000, 125 A (33801)



The picture may show a similar product.

### Description

Part No.: **33801** 000A

QUADRON<sup>®</sup>30Compact

NH fuse switch-disconnector size 000, 125 A

box terminal

connection top or bottom

for busbars 12 x 5, 10

with CrossLink<sup>®</sup>Technology

### System

30Compact 3P

### Advantages of the product

only 49.5 mm wide

rotatable for connection at bottom or top

**Product group** 09

**Subgroup** 22

pack size 1  
EAN 4021267338015

ETIM 5.0 EC001040  
ETIM 8.0 EC001040  
ETIM 10.0 EC001040

## Approvals

### Standards

IEC 60947-1:2020  
IEC 60947-3:2020 AC ratings only

type number: QU-NH000

## Technical data

for fuse links size:	NH 000
fuse links acc. to standard:	IEC / HD 60269-2
permitted power dissipation of the fuse-link:	9 W
requirements for contact parts:	Fuse links with silver-plated contact pieces recommended. For fuse links with nickel-plated contact pieces, a reduction factor of 0.8 is to be observed.

### Details IEC

#### Standards

IEC 60947-1:2020  
IEC 60947-3:2020 AC ratings only

#### Electrical data IEC

rated current (IEC): 125 A  
rated voltage (IEC) AC: 690 V

rated voltage (IEC) DC: 440 V

rated isolation voltage  $U_i$  AC: 800 V  
rated isolation voltage  $U_i$  DC: 500 V  
rated surge voltage  $U_{imp}$ : 6 kV

Utilisation category AC (IEC 60947-3) : AC-21B (690 V / 80 A)  
AC-22B (400 V / 125 A)

cond. short-circuit current with fuses (AC): 50 kA / 690 V (80 A)  
50 kA / 500 V (100 A)  
80 kA / 400 V (125 A)  
100 kA / 400 V (100 A)

approved with fuse links of operation class: gG

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 6.7 W.

(The power dissipation at full load would be 10.5 W.)

### Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

max. permitted voltage (IEC) DC: 800 V

A fuse-combination unit acc. to IEC 60947-3 can only be operated at a higher voltage than its rated voltage, if it is used as a fuse-disconnector without breaking capacity, up to its max. rated insulation voltage and labelled as such.

In accordance with the specified AC and DC switching properties and in consideration of the overload conditions, certain distances to earthed metal parts are to be adhered to. detailed information upon inquiry

When several devices are used side-by-side in continuous operation, the rated load factor specified in IEC / EN 61439-1, Table 1, must be observed.

### Mechanical data

W x H x D: 49.5 x 175 x 127

weight: 52.5 kg/100

poles: 3-pole

for busbars: 12 x 5, 10

front degree of protection: IP30

vertical installation position: Yes

horizontal installation position: No

### Terminal points

cage clamp connection

screw drive: S4

wire stripping: 15 mm

min. cross-section: 2.5 mm<sup>2</sup>

max. cross-section: 50 mm<sup>2</sup>

re: 2.5 - 16 mm<sup>2</sup>

rm: 2.5 - 50 mm<sup>2</sup>

f: 2.5 - 50 mm<sup>2</sup>

f + AE: 1.5 - 50 mm<sup>2</sup>

(f + AE may not fit with max. cross-section)

Md min.: 4.0 Nm

Md max.: 5.0 Nm

Not suitable for aluminium cables !

Terminal space: 10x10

lam. Cu width: 6 - 10 mm

lam. Cu thickness: 2 - 10 mm

box terminal:

1.5 - 50 mm<sup>2</sup> flexible and flexible with wire-end ferrules\*

2.5 - 50 mm<sup>2</sup> flexible

2.5 - 16 mm<sup>2</sup> solid round

2.5 - 50 mm<sup>2</sup> stranded round

Terminal space 10 mm x 10 mm

(\*flexible cables of maximum cross-section may not fit when using wire-end ferrule)

### Material properties

halogen-free: Yes

## Application notes

Not suitable for aluminium cables !

A fuse-combination unit acc. to IEC 60947-3 can only be operated at a higher voltage than its rated voltage, if it is used as a fuse-disconnector without breaking capacity, up to its max. rated insulation voltage and labelled as such.

permitted power dissipation of the fuse-link: 9 W

requirements for contact parts: Fuse links with silver-plated contact pieces recommended.

For fuse links with nickel-plated contact pieces, a reduction factor of 0.8 is to be observed.

## Accessories

further accessories

<https://pim.woehner.de/EN/EN/1000213787>