

insulator (05792)



The picture may show a similar product.

Description

Part No.: **05792 000**

insulator

with female thread at both sides, length across flats 30

M8 x 30

Product group 06

Subgroup 89

pack size 20

EAN 4021267057923

ETIM 5.0 EC001166

ETIM 8.0 EC001166

Approvals

Standards

IEC 61439-1:2020

CCC approval: no certification required

Technical data

Details IEC

Standards

IEC 61439-1:2020

Electrical data IEC

rated voltage (IEC) AC: 1500 V

rated voltage (IEC) DC: 1500 V

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 0.0 W.

(The power dissipation at full load would be 0.0 W.)

Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

min. permitted operation temperature -40°C

max. permitted operation temperature 130°C

Mechanical data

W x H x D: 30 x 30 x 30

weight: 5.3 kg/100

Terminal points

female thread

M8

Material properties

halogen-free: Yes

Application notes

The installation of the insulator is required on a flat surface on both sides. The fixing screw must be fixed on both surfaces.

The installation on a non-flat mounting surface leads to inadmissible tensions which could cause damages to the insulator.

no data

<https://pim.woehner.de/EN/EN/1000045119>