


## busbar adapter 115 A, 3-pole (32034)



The picture may show a similar product.

### Description

Part No.: **32034 000A**

EQUES<sup>®</sup> 60Classic

busbar adapter 115 A, 3-pole

for Schneider Electric GV4

81 x 200, with leads AWG 4 (25 mm<sup>2</sup>), top connection to the system

for Schneider Electric TeSys GV4

for busbars 12, 15, 20, 25, 30 x 5, 10 and section busbars

### System

60Classic

### Advantages of the product

Conductor ends ultrasonically sealed.

Click mechanism when pushing onto the busbar.

**Product group** 05

**Subgroup** 28

pack size 1  
EAN 4021267320348

ETIM 5.0 EC001531  
ETIM 8.0 EC001531

## Approvals

### Standards

IEC 61439-1:2020  
UL 508

### Approvals

CSA , UL



for UL feeder circuits >250V

type number: EEC60100-L

UL file: E123577, UL category (for USA): NMTR <https://www.ul.com>  
UL file: E123577, UL category (for Canada): NMTR7 <https://www.ul.com>  
CSA file: 110285, CSA class: 3211-37 <https://directories.csa-international.org>  
CCC approval: no certification required

## Technical data

### Details IEC

#### Standards

IEC 61439-1:2020

#### Electrical data IEC

rated current (IEC): 115 A  
rated voltage (IEC) AC: 690 V

rated isolation voltage  $U_i$  AC: 800 V  
rated surge voltage  $U_{imp}$ : 6 kV

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 4.6 W.

(The power dissipation at full load would be 7.3 W.)

### Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

min. permitted operation temperature -40°C

### Details UL

#### Standards

UL 508

for UL feeder circuits >250V

### Electrical data UL

rated current (UL): 100 A

rated voltage (UL) AC: 600 V

rated frequency (UL): 50 / 60 Hz

SCCR: 18 kA with Schneider TeSys GV4 100 A / 480 V AC

14 kA with Schneider TeSys GV4 100 A / 600 V AC

### Mechanical data

W x H x D: 81 x 200 x 68

weight: 54.5 kg/100

poles: 3-pole

for busbars: 12, 15, 20, 25, 30 x 5, 10 and section busbars

### Material properties

halogen-free: Yes

## Application notes

There must be a clearance of at least 12 mm above the article to remove it from the busbar system.

the short-circuit capacity of the combination of adapter and MCCB depends on the MCCB

for UL feeder circuits >250V

<https://pim.woehner.de/EN/EN/1000230952>