

component support (32311)



The picture may show a similar product.

Description

Part No.: **32311** 000A

EQUES® CrossBoard

component support

without electrical connection, 1 fixed mounting rail

18 x 160

for busbars 12, 15, 20, 25, 30 x 5, 10 and section busbars
with CrossLink® interface

System

CrossBoard® 125A / 250A, CrossBoard® 800 A

Product group 05

Subgroup 17

pack size 6

EAN 4021267323110

ETIM 5.0 EC001531

ETIM 8.0 EC001531

Approvals

Standards

IEC 61439-1:2020

UL 508

Approvals

UL



for UL feeder circuits >250V

type number: EQ18-A0

UL file: E123577, UL category (for USA): NMTR <https://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <https://www.ul.com>

CCC approval: no certification required

Technical data

Details IEC

Standards

IEC 61439-1:2020

Electrical data IEC

rated voltage (IEC) AC: 690 V

rated isolation voltage U_i AC: 800 V

rated surge voltage U_{imp} : 6 kV

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 0.0 W.

(The power dissipation at full load would be 0.0 W.)

Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

min. permitted operation temperature -40°C

Details UL

Standards

UL 508

for UL feeder circuits >250V

Mechanical data

W x H x D: 18 x 160 x 35

weight: 5.0 kg/100

for busbars: 12, 15, 20, 25, 30 x 5, 10 and section busbars

Material properties

halogen-free: Yes

Application notes

not applicable, since the product does not contain or carry any live parts or is not stressed in the case of a short-circuit

for UL feeder circuits >250V

Accessories

further accessories



31390 000

set of connectors

connector to create multipole adapters (100 pieces)

for 50 connections

<https://pim.woehner.de/EN/EN/1000204609>