


NH fuse switch-discon. size 3, 630 A, panel mounting (33203)



The picture may show a similar product.

Description

Part No.: **33203** 000

QUADRON[®] Panel

NH fuse switch-discon. size 3, 630 A, panel mounting

Size NH 3

screw M12

for mounting plate

System

Panel

Advantages of the product

Disconnectors are equipped with arc chambers.

The shock protection is split into 2 for safe connection of the conductors.

Self-closing inspection holes, which can be punched out, are available in the cover.

Product group 09

Subgroup 12

pack size 1
EAN 4021267332037

ETIM 5.0 EC001040
ETIM 8.0 EC001040

Approvals

Standards

IEC 60947-1:2020
IEC 60947-3:2020 AC ratings only
UL 4248-1

Approvals

IEC (CB) , UL , CCC , DNV GL



for UL feeder circuits >250V

type number: LTS-3

UL file: E230163, UL category (for USA): IZLT2 <https://www.ul.com>
CCC certificate: 2004010302117263

Technical data

for fuse links size:	NH 3
fuse links acc. to standard:	IEC / HD 60269-2
permitted power dissipation of the fuse-link:	48 W
requirements for contact parts:	Fuse links with silver-plated contact pieces recommended. For fuse links with nickel-plated contact pieces, a reduction factor of 0.8 is to be observed.

Details IEC

Standards

IEC 60947-1:2020
IEC 60947-3:2020 AC ratings only

Electrical data IEC

rated current (IEC): 630 A

rated voltage (IEC) AC: 690 V

rated voltage (IEC) DC: 440 V

rated isolation voltage U_i AC: 800 V

rated isolation voltage U_i DC: 500 V

rated surge voltage U_{imp} : 6 kV

Utilisation category AC (IEC 60947-3): AC-22B (690V/ 630A)

AC-22B (800V/ 315A)

AC-23B (690V/ 500A)

AC-23B (500V/ 630A)

cond. short-circuit current with fuses (AC): 50 kA / 690 V

approved with fuse links of operation class: gG

rated peak withstand current I_{pk} max.: 35.2 kA

rated short-time withstand current I_{CW} (1.0 s) max.: 15.1 kA

I_{CW} approved with: Trennmesser

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 23.0 W.

(The power dissipation at full load would be 36.0 W.)

Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

max. permitted voltage (IEC) DC: 800 V

further utilisation category AC (IEC 60947-3):

AC-20B (1000V) bei Verschmutzungsgrad 2

further utilisation category DC (IEC 60947-3):

DC specifications: 2 current paths (L1,L3) in series

DC-22B (440V)

DC-21B (440V)

DC-20B (1000V) at pollution degree 2

visible information required if used at more than 440V

DC: do not switch under load

A fuse-combination unit acc. to IEC 60947-3 can only be operated at a higher voltage than its rated voltage, if it is used as a fuse-disconnector without breaking capacity, up to its max. rated insulation voltage and labelled as such.

min. permitted operation temperature -40°C

max. permitted operation temperature 55°C

Entsprechend den angegebenen AC- und DC- Schalteigenschaften und unter Berücksichtigung der Überlastbedingungen, sind gewisse Abstände zu geerdeten Metallteilen einzuhalten. Nähere Informationen auf Anfrage.

Bei Verwendung als Trennschalter ist die Einhaltung der Abstände nicht erforderlich.

Degree of protection IP30 at front, degree of protection near terminal depends on installation

Details UL

Standards

UL 4248-1

for UL feeder circuits >250V

Electrical data UL

rated current (UL): 600 A

rated voltage (UL) AC: 600 V

rated frequency (UL): 50 / 60 Hz

SCCR: 100 kA

Mechanical data

W x H x D: 256 x 300 x 143

weight: 490.0 kg/100

poles: 3-pole

Mounting: for mounting plate

front degree of protection: IP30

Terminal points

screw connection

M12

screw drive: SW18

Md min.: 35.0 Nm

Md max.: 40.0 Nm

Not suitable for aluminium cables !

Material properties

halogen-free: Yes

Application notes

Not suitable for aluminium cables !

based on the AC and DC switching capacities and considering the overload conditions as given in the above mentioned standards the following distances to earthed metal parts have to be respected:

required spacing top: 50 mm

required spacing at sides: 30 mm

A fuse-combination unit acc. to IEC 60947-3 can only be operated at a higher voltage than its rated voltage, if it is used as a fuse-disconnector without breaking capacity, up to its max. rated insulation voltage and labelled as such.

permitted power dissipation of the fuse-link: 48 W

requirements for contact parts: Fuse links with silver-plated contact pieces recommended.

For fuse links with nickel-plated contact pieces, a reduction factor of 0.8 is to be observed.

for UL feeder circuits >250V

Accessories

connection accessories



33147 000

prism terminal, double, for Cu cables
2x 150 mm²
size 3



33165 000

clamp connector for Cu cables
150 - 300 mm²
for: QCB-NH2, LTS-F 400, LTS 630



33168 000

prism terminal, single, for Cu and Al cables
150 - 300 mm²
size 3



33385 000


prism terminal, double, for Cu cables
2x 185 mm²
size 3



33272 000


extension for 2 cable lugs
size 3

covers



33144 000

cover for cable lugs, top / bottom attachable
for QCB-NH3
for: QCB-NH3



33154 000
trim frame, single
290 x 330
size 3



33155 000
barrier for handle
for NH fuse-switch disconnecter size 1-3
for closing of handle area from rear



33419 000
connection shroud
for NH fuse-switch-disconnector size 3, max. 600 A

further accessories



33156 000
pilot switch
changeover 250 V AC / 5 A, 30 V DC / 4 A



33157 000
lid interlock
for sealing wire or 3 padlocks with shackle of 4 - 7 mm
Size 1 - 3

<https://pim.woehner.de/EN/EN/1000046865>